

L1® PORTABLE LINE ARRAY SYSTEMS

Bose® L1 portable line array systems use proprietary technology to deliver clear, powerful sound throughout the entire listening area – even off to the extreme sides. The combination of performance, portability and easy setup makes L1 systems well-suited for any event that requires professional sound.



L1 Model II system



L1 Model IS system



L1 Compact system

	L1 Model II system	L1 Model IS system	L1 Compact system
Positioning	Our most advanced system featuring our 24-speaker articulated line array providing our best tonal balance, coverage and highest output.	A unique combination of performance and portability that includes our 12-speaker articulated line array providing smooth tonal balance, coverage and high output.	Our smallest, lightest and easiest-to-set-up L1 system featuring a 6-speaker curved articulated line array providing smooth tonal balance and coverage, weighing just 29 pounds.
Audience Size	Up to 500	Up to 300	Up to 100
Applications	<ul style="list-style-type: none"> • Musicians • Mobile DJs • Public Speaking • Professional A/V Applications 		<ul style="list-style-type: none"> • Acoustic Musicians • Secondary PA for Mobile DJs • Public Speaking • Business Presentations/Classrooms • Backyard Parties
Array Performance	The articulated 24-speaker line array provides 180 degrees of horizontal sound coverage, while at the same time offering extremely tight vertical control resulting in less drop-off in volume over distance than conventional loudspeakers.	The 12-speaker articulated line array provides 180 degrees of horizontal sound coverage, while at the same time offering tight vertical control resulting in less drop-off in volume over distance than conventional loudspeakers.	The L1 Compact loudspeaker array is smaller than those in the L1 Model IS and Model II systems, yet produces comparable horizontal sound coverage. The L1 Model IS and Model II systems project sound further and with less volume drop-off than the L1 Compact system.
Coverage	180° H x 0° V	180° H x 10° V	180° H x 40° V
Max SPL	115 dB (Continuous), 121 dB (Peak)	112 dB (Continuous), 118 dB (Peak)	106 dB (Continuous), 112 dB (Peak)
Low-Frequency (-3dB)	40 Hz (with B1 or B2)		65 Hz
Bass	The Model II power stand can drive 2 B1s or a single B2 bass loudspeaker. It also features a dedicated bass line out, allowing it to be used with the AI Packlite® amplifier to add two additional B1 bass modules or an additional B2 bass module.	The Model IS power stand can drive 2 B1s or a single B2 bass module.	The L1 Compact system features an integrated bass speaker in the power stand. <i>Not compatible with the B1 or B2 bass modules.</i>
I/O	<ul style="list-style-type: none"> • 1 x 1/4" analog input • 1 x NL4 bass module out • 1 x 1/4" bass line out • 1 x ToneMatch® port • 1 x trim control • 1 x power switch 	<ul style="list-style-type: none"> • 1 x 1/4" analog input • 1 x NL4 bass module out • 1 x ToneMatch port • 1 x trim control • 1 x power switch 	<ul style="list-style-type: none"> • 1 x microphone input • 1 x 1/8" balanced analog input • 1 x RCA stereo input • 1 x 1/4" analog input • 1 x 1/4" mono analog output • 1 x RCA output
System Includes	<ul style="list-style-type: none"> • L1 Model II top and bottom loudspeaker arrays • L1 Model II system power stand • AC power cord • Protective carrying bags/covers • B1 or B2 bass module with cable and slip cover 	<ul style="list-style-type: none"> • L1 Model IS top array and bottom extension • L1 Model IS power stand • AC power cord • Protective carrying bags/covers • B1 or B2 bass module with cable and slip cover 	<ul style="list-style-type: none"> • L1 Compact loudspeaker array • L1 Compact system power stand with slip cover • L1 Compact system extensions with protective carry bag

©2012 Bose Corporation. All information subject to change without notice. C_011277